


## 29 138 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 3 VALVES



### PRODUCT DESCRIPTION

- Colour: chrome
- Set for final installation for
- Required rough-in-set sold separately (GROHE Rapido SmartBox 35 601 000)
- Metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), 6° angle adjustable
- 10 mm thin profile escutcheon
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to Full Flow
- exchangeable symbols
- GROHE TurboStat Compact cartridge with wax thermoelement
- GROHE SafeStop safety button at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- Built-in check valve with dirt strainer
- Multiple outlets can be run simultaneously
- Requires Rough-In Set (29 038 001) (sold separately)
- • Maximum flow performance combined: 9.5gpm (36L/min) @ 43.5 psi (3 bar)
- • Optional flow reducer for CALGreen compliance included

## 29 138 000 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH 3 VALVES



### SPARE PARTS, September 2016 – spareParts.validDate.now

- 1: Mounting plate (Order-nr. 48362000)
  - 2: Temperature control handle (Order-nr. 49029000)
  - 2.1: Cover cap (Order-nr. 1015030000)
  - 2.2: handle adaptor (Order-nr. 1015059990)
  - 3: Escutcheon (Order-nr. 49048000)
  - 4: Push button (Order-nr. 48361000)
  - 4.1: pushbutton (Order-nr. 14077000)
  - 5: Cartridge (Order-nr. 48359000)
  - 5.1: Spindle (Order-nr. 49088000)
  - 6: 3/4" Thermostatic compact cartridge (Order-nr. 49028000)
  - 7: Non-return valves (Order-nr. 47979000)
  - 8: Seal (Order-nr. 48360000)
  - 9: Socket spanner (Order-nr. 49059000)\*
  - 10: 3/4" Reversed TurboStat Cartridge (Order-nr. 49003000)\*
  - 11: <strong>Service Stops</strong> (Order-nr. 1405300M)\*
  - 12: Universal extension set single-lever mixers, 25 mm (Order-nr. 14048000)\*
- \* Optional accessories